













Maximum suggested horsepower ► **70 HP**

	Total width
	Working width
	Side-shift
	Min. suggested horsepower
	Weight
	Number of blades

B						
	in	in	in-in	HP	lbs	Nr.
105	49	43	22 - 28	35	717	24
130	59	53	26 - 26	40	805	30
155	69	63	31 - 31	45	893	36
180	79	73	36 - 36	55	981	42
205	89	83	41 - 41	60	1080	48

B

The rotary tiller model **B** is one of the most tested and reliable among the Celli machines. At least 15,000 units have been sold all over the world to be used in a variety of working situations and in very different soil conditions.

High quality technical solutions have been adopted: box section frame, special sealing system to protect the rotorshaft bearings, sturdy gearbox designed and built by Celli, thick rear cover well shaped to get an ideal finishing and levelling of the soil.

FIXED ROTARY TILLER



TECHNICAL SPECIFICATIONS

- Maximum horsepower 70 HP
- 4 speed gearbox for 540 rpm PTO
- Gear side drive
- 3 point hitch cat. 3
- L-shaped blades: 80x7 mm (6 blades each flange, side blades leaning inwards)
- Working depth about 8.6"
- Rear tailgate adjustment by chain
- Food stand
- Drive shaft with clutch
- Removable safety protections

OPTIONAL ACCESSORIES

- 1 speed gearbox (184 rpm) for 540 rpm PTO
- C-shaped blades
- Side blades leaning outwards
- Off-set version Bolted double flanges
- Rear rollers at origin
- Higher gearbox support