













Maximum suggested horsepower

▶ **45 HP**

**DELTA**  
IRRIGATION

	Total width
	Working width
	Side-shift
	Min. suggested horsepower
	Weight
	Number of blades

F/BA	 in	 in	 in-in	 HP	 lbs	 Nr.
<b>105</b>	47	41	20 - 20	25	485	30
<b>125</b>	55	49	24 - 24	30	578	36
<b>145</b>	63	57	28 - 28	35	562	42
<b>165</b>	71	65	32 - 32	40	595	48

**F/BA**

The rotary tiller **F/BA** combine a modern design to high quality technical features, generally reserved to bigger models.

It is worth noting that the box section frame is made of a welded double plate to guarantee adequate resistance, the transmission gears are oversized, the rear cover is well shaped to get an ideal finishing and levelling of the soil.



**FIXED ROTARY TILLER**  
suitable for small size tractors

#### TECHNICAL SPECIFICATIONS

- Maximum horsepower 45 HP
- Rotor speed: 221 rpm (for 540 rpm PTO)
- Chain side drive
- 3 point hitch cat. 3
- L-shaped blades: 60x6 mm (6 blades each flange, side blades leaning inwards)
- Working depth about 7"
- Side-skids
- Food stand
- Drive shaft without safety device
- Removable safety protections

#### OPTIONAL ACCESSORIES

- 4 speed gearbox for 540 rpm PTO
- C-shaped blades
- Side blades leaning inwards
- Set of 2 front wheels
- Extended upper and lower 3 point hitch
- Drive shaft with shear bolt
- Drive shaft with clutch

