

Maximum suggested horsepower

70 HP - 51 KW



DELTA
IRRIGATION

	Total width
	Working width
	Min. suggested horsepower
	Weight
	Maximum working depth
	Number of spades

Y70										
	IN	CM	IN	CM	HP/KW	LBS	KG	IN	CM	
100	41	103	39	100	30/22	1014	460	12	30	4
115	46	118	45	115	30/22	1058	480	12	30	4
130	55	140	54	137	35/26	1235	560	12	30	6
145	60	152	59	149	35/26	1301	590	12	30	6
160	66	167	65	164	40/29	1356	615	12	30	6
175	72	183	71	180	50/37	1587	720	12	30	8
190	79	201	78	198	55/40	1653	750	12	30	8
205	81	207	80	204	60/44	1720	780	12	30	8

Y70

SPADING MACHINE



Suitable for glasshouses and orchards

THE CONCEPT

Spading machines are tillage equipment largely appreciated in several working conditions and applications, such as:

- to work without any problem in extremely wet soil.
- to work up to a maximum working depth of 30 cm
- to remove the bottom soil hardpan, that is the layer of compacted soil in depth

- Also it require low traction power thus it efficiently ab-sorbs the tractor power.
- Do not compact the soil
- to partially lay underground crop residues without throw-ing the clods back complete-ly.
- to limit soil erosion and also the wash away of light and steeply sloping soil, because the tilled soil is composed of medium size clods.

TECHNICAL SPECIFICATIONS

- maximum horse power: 70 HP (51 KW)
- 4 speed gearbox for 540 rpm PTO
- grease lubrication
- 3 point hitch cat.2
- rear tailgate with levelling flap
- working depth adjustment by skids
- drive shaft with clutch
- spades: 210x162 mm (models 100-130-145-175-190); 210x192 mm (models 115-160-205)
- safety protections